



VCI EMITTING SYSTEMS & ELECTRONIC PRODUCTS

VCI-150 & VCI-170

PRODUCT DESCRIPTION

VCI-150 and VCI-170 tapes are unique emitting devices designed to provide corrosion protection for metal components and parts enclosed in non-ventilated control boxes, cabinetry or tool boxes. VCI-150 protects up to 0.4 cubic foot (11.3 liters) per linear inch (2.5 cm) and VCI-170 protects up to 1 cubic foot (28.3 liters) in volume per linear inch (2.5 cm). The VCI emits vapors which deposit a molecular layer on internal metal surfaces to protect critical, complex and expensive electronic equipment during operation, shipping or storage. VCI-150 and VCI-170 are patented foam tapes from which the corrosion inhibitor is slowly released and moisture can be absorbed. They provide long-term protection against corrosion even in the presence of adverse conditions including salt, moisture, airborne contaminants, H₂S, SO₂, NH₃ and others.

TYPICAL APPLICATIONS

VCI-150 and VCI-170 can be effectively used for all operating, packaged and stored electrical equipment, marine navigation and communication equipment, aerospace electrical controls, electric motors, switching equipment, fuseboxes, power boxes, medical equipment, electrical wireways, terminal boxes, scientific and measuring instruments, telecommunications equipment and remote electronic devices.

FEATURES

- Economical to use.
- Very convenient to install.
- Provides continuous protection up to 24 months.
- Effective in polluted and humid environments.
- Does not interfere with electrical, optical and mechanical surface performance.
- Multimetal performance.
- Protects during operation and shutdown.
- Non-toxic and safe to handle.
- Compact, space-saving, inobtrusive device.
- Free of nitrites, silicones, phosphates.
- USDA and FDA approved for indirect use on food processing and packaging equipment.
- Approved for U.S. military use: NATO# 8030-00-244-1299

- No spraying, wiping or dipping required.
- Low VOC values, meets Southern California Clean Air Act and other local regulations.
- Ability to wick away moisture.

METHOD OF APPLICATION

VCI-150 and VCI-170 are extremely simple and convenient to install. The tapes should be installed as soon as possible. Simply select a space within any enclosed system where corrosion protection would be useful. Verify the surface to which the tape will be installed is clean and free of debris. Peel off the protective peel strip from the bottom of the tape and attach it to the clean surface. The VCI-150 and VCI-170 tapes can be installed in any position. If the enclosure is not totally airtight, or if the access doors are opened frequently, replace the VCI-150 and VCI-170 tape more often than every 2 years. After periods of heavy maintenance replace the tape and spray the enclosure very lightly with VCI-238 Aerosol, corrosion inhibiting cleaner/protector.

SPECIFICATIONS

VCI-150 Tape (Foam tape with adhesive backing)	
Packaging	6 rolls packaged in resealable poly bags per carton
Protection	0.4 ft. ³ (11 liters) per linear inch (per 2.5 cm)
Standard Size	12' L x 3/4" W x 1/4" H (3.6 m x 19 mm x 6 mm)
VCI-170 Tape (Foam tape with adhesive backing)	
Packaging	1 roll packaged in a resealable poly bag per carton
Protection	1 ft. ³ (28.3 liters) per linear inch 2.5 cm)
Standard Size	20' L x 2" W x 1/4" H (6.1 m x 51 mm x 6 mm)



CORTEC
CORPORATION

Environmentally Safe VCI/MCI® Technologies

KPR TOLL FREE CUSTOMER SERVICE
1-866-577-2326

FOR INDUSTRIAL USE ONLY
KEEP OUT OF REACH OF CHILDREN
KEEP CONTAINER TIGHTLY CLOSED
NOT FOR INTERNAL CONSUMPTION
CONSULT MATERIAL SAFETY DATA SHEET FOR
MORE INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement product shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by: KPR ADCOR INC.
Phone (905) 628-3232, Fax (905) 628-2529
Toll Free (866) kpr--adcor, E-mail info@corrosionVCI.com
Internet <http://www.corrosionVCI.com>

printed on recycled paper 10% post consumer

Revised 2/98. Cortec®, Corwipe®, EcoSpray/EcoClean®, EcoWeave®, MCI®, Cor-Lube™, Cor-Mastic™, Cor-Pak™, Corrosorb™, EcoCoat™, EcoShield™, Electricor™, Migrating Corrosion Inhibitors™, Migratory Corrosion Inhibitors™, Primecoat™, Total Corrosion Control™, VCI Film Color of Blue™ and VHDRS™ are trademarks of Cortec Corporation.
© Cortec Corporation 1998. All rights reserved.



Certificate No. 43345