

Distributed by: KPR ADCOR INC.
 'We Stop Rust!' TM
 WWW.CORROSIONVCI.COM

Toll free: (866) 577-2326
 Tel: 905-628-3232
 Fax: 905-628-2529

Web site: www.corrosionvci.com
 Email: KPR@CORROSIONVCI.COM

DAUBERT VCI® NOX-RUST® LIQUID 7800

Corrosion Preventative Liquid, Lubricating
 (Federal Specification VV-L-800 Type Product)

General Information

Daubert VCI Nox-Rust 7800 liquid when applied to steel, provides up to six months inside protection and when packaged will give as much as 12 months protection against corrosion. Nox-Rust 7800 differs from ordinary corrosion preventive liquids in that it is also an excellent lubricant. In general, this material is used on high precision equipment, assemblies and parts, and need not be removed and replaced with conventional lubricants.

Nox-Rust 7800 is formulated to fulfill the requirements of the Federal Specification noted above. It meets the military requirement of good protection against rust and is designed to give special lubrication properties (such as to insure easy operation of machine guns at sub-zero temperatures, or for the breaking in, storage and operation of engines).

Nox-Rust 7800 has excellent oxidation resistance and no corrosive effect on non-ferrous metals.

The conformance of this product to rigid government specifications insures the commercial user the best in performance and quality.

General Uses

Nox-Rust 7800 is a light preservative oil especially suited for precision instruments, firearms, antique typewriters and other close tolerance mechanisms as well as for their individual components.

Typical Properties

Application	Flush, dip, spray or brush
Removal	*Petroleum solvents
Coverage	2,000 sq. ft. per gallon (49.1 sq. meters per liter)
Viscosity	SUS @ 100°F. 66-70 CTS @ -65°F. 60,000
Flash point, min.	275°F. (135°C)
Pour point	-70°F. (-56.67°C)
Effect on non-ferrous metals	None
Lbs./Gallon	7.4
Specific gravity	0.889

* Removal is rarely required, except in some instances when metal is to be painted.

Protective Properties (Typical Batch)

Inside, not packaged	5 - 6 months
Inside, packaged	6 - 12 months
Accelerated Test, 100% RH @ 120°F	200 hours

Available in 53 gallon drums and 5 gallon pails.

NOX-RUST® 7800

The data, statements and recommendations in this product information sheet are based on testing, research and other development work, which has been carefully conducted by us, and we believe such data, statements and recommendations will serve as reliable guidelines. Physical properties shown above represent typical values and are not intended for use in writing specifications. However, this product is subject to numerous uses under varying conditions over which we have no control, and accordingly, we do NOT warrant that this product is suitable for any particular use. Users are advised to test the product in advance to make certain it is suitable for their particular production conditions and use.

WARRANTY – All products manufactured by us are warranted to be first class material and free from defects in material and workmanship. Liability under this warranty is limited to the net purchase price of any such products proven defective or, at our option, to the repair or replacement of said products upon their return to us transportation prepaid. All claims on defective products must be made in writing within 30 days after the receipt of such products in your plant and prior to further processing or combining with other material and products.

WE MAKE NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY OF ANY OF OUR PRODUCTS FOR ANY PARTICULAR USE, AND WE SHALL NOT BE SUBJECT TO LIABILITY FROM ANY DAMAGES RESULTING FROM THEIR USE IN OPERATIONS NOT UNDER OUR DIRECT CONTROL.

THIS WARRANTY IS EXCLUSIVE OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, AND NO REPRESENTATIVE OF OURS OR ANY OTHER PERSON IS AUTHORIZED TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF OUR PRODUCTS.